

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
23 June 2005 (23.06.2005)

PCT

(10) International Publication Number
WO 2005/057761 A1

(51) International Patent Classification⁷: **H02K 37/04**

(74) Agent: HAW, Yong-Noke; 8th Fl. Songchon Bldg.,
642-15, Yoksam-dong, Kangnam-gu, Seoul 135-080 (KR).

(21) International Application Number:
PCT/KR2004/003225

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG,
MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,
PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN,
TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 9 December 2004 (09.12.2004)

(25) Filing Language: Korean

(26) Publication Language: English

(30) Priority Data:
10-2003-0088878
9 December 2003 (09.12.2003) KR

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (for all designated States except US): LG
INNOTEK CO.,LTD [KR/KR]; 14th Fl. Hansol Bldg.,
736-1, Yoksam-dong, Kangnam-gu, Seoul 135-082 (KR).

(72) Inventors; and


(75) Inventors/Applicants (for US only): SON, Young-Kyu
[KR/KR]; 108-503 Sunkyung Apt. Wolgae-dong,
Gwangsan-gu, Gwangju-si, 506-772 (KR). YANG,
Eung-Mo [KR/KR]; 405-1704 Joogong 4, Woon-
nam-dong, Gwangsan-gu, Gwangju-si, 506-765 (KR).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: STEPPING MOTOR BEING CONVENIENTLY ASSEMBLED AND FABRICATION METHOD OF THE SAME



(57) Abstract: A stepping motor includes a bracket, a housing having a first end coupled to the bracket and a second end having a reduced width compared with the first end, a stator disposed in the housing to form electric field, a first supporting unit formed on a first end of the bracket, a magnet fixed corresponding to the stator to provide the electric field, a second supporting unit supported on the second end of the housing, a rotor supported by the first and second supporting units, and a stopper fitted on an opened end of the second end of the housing to support the second supporting unit.

WO 2005/057761 A1

WO 2005/057761

PCT/KR2004/003225

STEPPING MOTOR BEING CONVENIENTLY ASSEMBLED AND FABRICATION METHOD OF THE SAME

Technical Field

5 The present invention relates to a stepping motor, and more particularly, to a stepping motor and method for making the same, in which the assembling of the stepping motor can be easily conveniently performed. The present invention further relates to a stepping motor and method for making the same, in which the stepping motor is designed in a simple structure and the number of parts is reduced, thereby making it convenient to assemble the stepping motor and reducing the number of connecting portions to improve the precision of the stepping motor.

Background Art

15 A stepping motor has been applied to a variety of fields such as a floppy disk driver, a printer, a servomechanism, and the like. The stepping motor includes a shaft, a lead screw formed on a first end of the shaft, a magnet fixed on a second end of the shaft, and a stator applying electric field around the magnet. The shaft functions as a rotor cooperating with the stator. A transfer member is engaged with the lead screw. Accordingly, when the lead screw rotates, the transfer member reciprocates.

20 The operation of the stepping motor will be described hereinafter briefly. The shaft rotates by electromagnetic force generated between the magnet and the stator. When the shaft rotates, the lead screw rotates together with the shaft. At this point, the transfer member coupled to the lead screw moves in a direction of axis thereof.

30 Formed on opposite ends of the shaft are bearings supporting the shaft and preventing the shaft from being removed. The bearing has a complicated structure composed of balls, springs and guides.

35 In an assembling process of the stepping motor, the

above-described parts are connected to each other. Therefore, after the assembling process is finished, there may be interference between the parts adjacent to the shaft, thereby deteriorating the rotational performance of the motor and reducing the service life of the motor.

Furthermore, the connection processes between the many parts makes it complicate to assemble the stepping motor, thereby deteriorating the working efficiency.

10 Disclosure

Technical Problem

Accordingly, the present invention is directed to a stepping motor and method for making the same that substantially obviates one or more of the problems due to limitations and disadvantages of the related art.

An object of the present invention is to provide a stepping motor and method for making the same, which can simplify the assembling process by improving a supporting structure of a bearing and reducing the number of parts.

Another object of the present invention is to provide a stepping motor and method for making the same, which can improve the operational reliability by simplifying a shaft supporting structure to increase the assembling precision between the parts and improving the coaxiality of the stepping motor.

Technical Solution

To achieve these and other advantages and in accordance with the purpose of the present invention, as embodied and broadly described, there is provided a

According to another aspect of the present invention, there is provided a stepping motor comprising: a bracket; a housing having a first end coupled to the bracket and a second end having a reduced width compared with the first end; a stator disposed in the housing to form electric field; a first supporting unit formed on a first end of the bracket;

a magnet fixed corresponding to the stator to provide the magnetic field; a second supporting unit supported on the second end of the housing; a rotor supported by the first and second supporting units; and a stopper fitted on an opened
5 end of the second end of the housing to support the second supporting unit.

According to another aspect of the present invention, there is provided a stepping motor comprising: a housing provided with a guide portion for guiding a second supporting
10 unit; a stator installed in the housing to form electric field; a rotor rotatably supported by the second supporting unit and inserted to be spaced away from the stator; a magnet fixed on the rotor to correspond to the stator; and a bracket having a third supporting unit in which a first side of the
15 rotor is inserted, contacting an opening portion of the housing and a first supporting unit on which a second side of the rotor is rotatably supported.

According to still another aspect of the present invention, there is provided a method for making a stepping
20 motor, comprising the steps of: aligning a bracket and a single body housing using a pin; coupling the single body housing to the bracket; inserting a rotor in the housing and the bracket; and aligning a supporting unit on an end of the rotor.

25

Advantageous Effects

According to the present invention, the assembling precision can be improved by simplifying the shaft supporting structure. In addition, by integrally forming a bearing
30 guide function on a housing, the number of parts can be reduced, thereby simplifying the assembling process.

Furthermore, by assembling tooth yokes in an integral housing, the concentric precision between the tooth yokes is improved, thereby improving a drooping phenomenon of a rotor
35 as well as coaxiality and increasing the torque of the motor.

Description of Drawings

FIG. 1 is a sectional view of a stepping motor according to a preferred embodiment of the present invention;

5 FIG. 2 is an enlarged sectional view of a housing depicted in FIG. 1; and

FIG. 3 is a flowchart illustrating a method for making a stepping motor according to an embodiment of the present invention.

10 Best Mode for Carrying out the Invention

Hereinafter, preferred embodiments of the present invention will be described in detail with reference to accompanying drawings. While the present invention has been described and illustrated herein with reference to the
15 preferred embodiments thereof, it will be apparent to those skilled in the art that various modifications and variations can be made therein without departing from the spirit and scope of the invention. Thus, it is intended that the present invention covers the modifications and variations of this
20 invention that come within the scope of the appended claims and their equivalents.

FIG. 1 shows a sectional view of a stepping motor according to a preferred embodiment of the present invention and FIG. 2 shows an enlarged sectional view of a housing
25 depicted in FIG. 1.

Referring to FIGs. 1 and 2, the inventive stepping motor includes a bracket 140, a housing enclosing an outer circumference of a stator 120, a rotor 130, a first supporting unit 160, and a second supporting unit 170. The
30 bracket 140 defines a frame of the stepping motor so that the stepping motor can be installed on an object by the bracket 140. The housing is disposed around the stator 120 to protect a driving unit.

The bracket 140 is provided at a first end with a first
35 hooking part 142 bent in a vertical direction and at a second end with a second hooking part 141 bent in a vertical

direction. The first and second hooking parts 142 and 141 are respectively provided with penetrating holes 142a and 141a.

5 The rotor 130 includes a shaft 131 having a predetermined diameter and length, a lead screw 131a formed on an outer circumference of the shaft 131 to guide a transfer member in a reciprocal direction when the shaft 131 rotates by cooperating with the stator 120, a magnet 133 corresponding to the stator 120, and a magnet fixing end 131b
10 extending from an end of the shaft 131, the magnet 133 being provided on an outer circumference of the magnet fixing end 131b.

The shaft 131 included in a rotor 130, the magnet 133 and the magnet fixing end 131b are integrally rotated. The
15 stator 120 and the magnet 133 are spaced away from each other by a predetermined distance.

The first supporting unit 160 includes a pivot bearing 161 installed in the penetrating hole 142a of the first hooking part 142 and a ball bearing 163 mounted on a central
20 portion of the penetrating hole 142a.

The second supporting unit 170 includes a ball 173 roll-contacting a right end of the rotor 130, a thrust bearing 171 for axially supporting the ball 173, and a spring 175 elastically supporting the thrust bearing 171 to absorb
25 impact. The rotor 130 is supported at its opposite ends by the first and second supporting units 160 and 170, thereby accurately maintaining a concentric axis.

The stator 120 is provided in the housing 110 to form electric field, including coils 121a and 121b to which
30 electric current is applied, bobbins 123a and 123b around which the coils 121a and 121b are respectively wound, and a plurality of tooth yokes 125a, 125b, 125c, and 125d that are engaged with each other.

As another embodiment of the present invention, a third
35 supporting unit 150 including a supporting member 151

inserted in the second hooking part 141 may be further provided.

5 By the supporting member 151 inserted in the second hooking part 141, the coaxiality of the rotor 130 is improved, thereby generating high power torque from the stepping motor of the present invention.

The structure of the stepping motor will be described in more detail hereinafter.

10 The housing 110 defines a hollow portion 115. The housing is provided at a first end with an opening 113 engaging with the second hooking part 141 and at a second end with a guide portion for guiding the thrust bearing 171.

15 That is, the guide portion of the housing 110 is formed through a deep drawing process. The spring 175, the thrust bearing 171 and the ball 173 are disposed in the guide portion in a rightward order.

20 That is, the ball 173 roll-contacts the right end of the rotor 130 and the thrust bearing 171 supports the ball 173 in the axial direction. The spring 175 supports the thrust bearing 171 to absorb the impact generated by the rotation of the rotor 130. The thrust bearing 171 is inserted in the inner circumference of the guide portion 111.

25 A cap-shaped stopper 177 is coupled to the guide portion 111 to prevent the ball 173, the spring 175 and the thrust bearing 171 from being removed out of the guide portion 111.

30 A pocket 177a is depressed and inclined on the inner circumference of the stopper 177. When the stopper 177 is forcibly fitted or bonded in the guide portion 111, the pocket 177a functions to prevent foreign objects from being introduced into the housing 110.

The spring 175 may be formed of a coil spring and the thrust bearing 171 may be formed of synthetic resin.

35 As another embodiment, the supporting member 151 may be designed to directly support the rotor 130 by inserting

through the penetrating hole 141a of the second hooking part 141.

A method for making the stepping motor will be briefly described hereinafter.

5 The stator 120 is first mounted in the housing 110. Then, the housing 110 and the bracket 140 are aligned by a pin (not shown).

10 Next, an extreme end of the opening portion 113 of the housing is coupled to the second hooking part 141 of the bracket 140.

15 Then, the pin is removed and the rotor is inserted. The ball 173, the thrust bearing 171 and the spring 174 are installed in this order in the guide portion 111 of the housing 110. The stopper 177 is coupled to the end of the guide portion 111 to prevent the ball 173, the thrust bearing 171 and the spring 174 from being removed out of the guide portion 111, thereby finalizing the assembling of the stepping motor.

20 The assembling process will be described in more detail with reference to the accompanying drawing.

FIG. 3 shows a flowchart illustrating the assembling process of the stepping motor according to an embodiment of the present invention.

25 Referring to FIG. 3, a plurality of parts constituting the stator 120 are mounted on an inner surface of the hollow portion 115 of the housing 110 (S1), and the housing 110 and the bracket 140 are aligned by a center pin (not shown) such that the guide portion 111 of the housing 110 and the penetrating holes 142a and 141a formed on the respective first and second hooking parts 142 and 141 of the bracket 140 are aligned on a concentric axis (S2).

30 At this point, the penetrating holes 141a and 142a and the guide portion of the housing 110 are designed such that the inner diameters thereof are identical to each other. The center pin is designed such that an outer diameter thereof is identical to the inner diameter. As a result, when the

35

center pin is inserted, the bracket 140 and the housing 110 are accurately aligned on the coaxial direction.

After the above, the end of the opening portion of the housing 110 is coupled to the second hooking part 141 of the bracket 140 by welding or coking process (S3). At this point, since the bracket 140 and the housing 110 are aligned by the center pin, the coaxiality of the bracket 140 and the housing 110 is not deformed.

Next, the center pint is removed (S4) and the rotor 130 is inserted (S5).

Here, in order to assemble the stepping motor according to above-described alternative embodiment, the supporting member 151 may be inserted into the penetrating hole 141a before the rotor 130 is inserted. In this case, the center pin may not be used in order to align the bracket 140 and the housing 110 on a coaxial line.

Meanwhile, the inserted end of the rotor 130 is supported on the first supporting unit 160 by penetrating the second hooking part 141. As a result, when the rotor 130 is completely inserted, the stator 120 maintains a predetermined distance from the magnet fixing end 131b.

After the above, the thrust bearing 171 with the ball 173 and the spring 175 are installed in the guide portion 111 of the housing 110 (S6), and the cap-shaped stopper 177 is fitted on the guide portion 111 to prevent the bearing structure from be removed (S7).

As described above, when the assembling of the stepping motor is finished, the ball 173 contacts the magnet fixing end 131b as well as the thrust bearing 171. By the ball 173 contacting the thrust bearing 171, the rolling motion of the ball 173 becomes possible, thereby realizing the bearing operation. The load applied by the rotor 130 in an axial direction is attenuated by the spring 175, thereby maintaining the ideal coaxiality. Since the insertion end of the rotor 130 is supported by the first supporting unit 160,

the overall load generated by the rotor 130 in the axial direction can be fully supported.

According to the present invention, since the housing 110 is formed in a single body, the coaxiality is improved compared when a plurality of housings are formed. Furthermore, since the housing 110 is coupled to the bracket 140 by a single coupling process, the fraction defective caused during the assembling process of the stepping motor can be remarkably reduced.

In addition, by forming the guide portion for guiding the second supporting unit 170 on the housing 110, there is no need of any additional part for supporting the bearing. Furthermore, since the cap-shaped stopper 177 is easily coupled to the opened end of the guide portion 111, the assembling process of the stepping motor becomes more convenient.

Mode for Carrying out the Invention

Features of the present invention is in that the housing can be easily fixed on the bracket in a state where the housing is guided by the center pin and that the bearing structure is supported by the housing. It will be apparent to those skilled in the art that various modifications and variations can be made therein without departing from the spirit and scope of the invention.

Industrial Applicability

The present invention has advantages as follows:

1. The assembling precision can be improved by simplifying the shaft supporting structure.

2. By integrally forming a bearing guide function on a housing, the number of parts can be reduced, thereby simplifying the assembling process.

3. By assembling tooth yokes in an integral housing, the concentric precision between the tooth yokes is improved, thereby improving a drooping phenomenon of a rotor as well as

coaxiality and increasing the torque of the motor.

Claims

1. A stepping motor comprising:
a bracket;
5 a housing having a first end coupled to the bracket and
a second end having a reduced width compared with the first
end;
a stator disposed in the housing to form electric
field;
10 a first supporting unit formed on a first end of the
bracket;
a magnet fixed corresponding to the stator to provide
the magnetic field;
a second supporting unit supported on the second end of
15 the housing;
a rotor supported by the first and second supporting
units; and
a stopper fitted on an opened end of the second end of
the housing to support the second supporting unit.
20
2. The stepping motor according to claim 1, further
comprising a third supporting unit formed on a second end of
the bracket to support a point of the rotor.
- 25 3. The stepping motor according to claim 2, wherein
the third supporting unit comprises a hooking part formed by
bending the second end of the bracket and a supporting member
inserted in the hooking part.
- 30 4. The stepping motor according to claim 1, wherein
the housing is formed in a single body.
5. The stepping motor according to claim 1, wherein
the second supporting unit comprises a ball contacting an end
35 of the rotor;
a thrust bearing contacting the ball; and

a spring biased between the thrust bearing and the stopper.

5 6. The stepping motor according to claim 5, wherein the spring is formed of a coil spring.

7. The stepping motor according to claim 5, wherein the thrust bearing contacts the second end of the housing.

10 8. The stepping motor according to claim 5, wherein the thrust bearing is formed of synthetic resin.

15 9. The stepping motor according to claim 1, wherein the stopper is separately prepared and fitted on the second end of the housing.

10. The stepping motor according to claim 1, wherein the stopper is cap-shaped.

20 11. The stepping motor according to claim 1, wherein the stopper is forcibly fitted or bonded on the second end of the housing.

25 12. The stepping motor according to claim 1, wherein the first supporting unit comprises a hooking part defined by bending an end of the bracket and a bearing installed on a penetrating hole of the hooking part.

30 13. The stepping motor according to claim 1, further comprising a pocket formed on an inner surface of the stopper.

35 14. The stepping motor according to claim 1, wherein the stator and the magnet are paired and spaced from each other.

15. The stepping motor according to claim 1, wherein the first end of the housing is coupled to the bracket by a welding or caulking process.

5 16. The stepping motor according to claim 1, wherein the second end of the housing has a diameter identical to that of a penetrating hole formed on the bracket.

10 17. The stepping motor according to claim 1, wherein the rotor is supporting by the first and second supporting units.

18. A stepping motor comprising:
a housing provided with a guide portion for guiding a
15 second supporting unit;
a stator installed in the housing to form electric field;
a rotor rotatably supported by the second supporting unit and inserted to be spaced away from the stator;
20 a magnet fixed on the rotor to correspond to the stator; and
a bracket having a third supporting unit in which a first side of the rotor is inserted, contacting an opening portion of the housing and a first supporting unit on which a
25 second side of the rotor is rotatably supported.

19. The stepping motor according to claim 18, wherein the housing is formed in a single body.

30 20. The stepping motor according to claim 18, wherein the guide portion has a reduced diameter compared with the opened portion.

35 21. The stepping motor according to claim 18, wherein the third supporting unit comprises a hooking part having a penetrating hole and a supporting member inserted in the

penetrating hole.

22. The stepping motor according to claim 18, wherein
the second supporting unit comprises a ball contacting an end
5 of the rotor;

a thrust bearing contacting the ball; and

a spring disposed on a rear side of the thrust bearing
to attenuate impact from the thrust bearing.

23. The stepping motor according to claim 18, further
10 comprising a stopper coupled to the guide portion to support
the second supporting unit.

24. A method for making a stepping motor, comprising
15 the steps of:

aligning a bracket and a single body housing using a
pin;

coupling the single body housing to the bracket;
inserting a rotor in the housing and the bracket; and
20 aligning a supporting unit on an end of the rotor.

25. The method according to claim 24, further
comprising the step of removing the pin before inserting the
rotor into the housing and the bracket.

26. The method according to claim 24, wherein the
housing comprises a guide portion in which the supporting
unit is disposed.

27. The method according to claim 26, further
30 comprising the step of fixing a stopper on the guide portion
after aligning the supporting unit.

28. The method according to claim 24, wherein the
35 bracket and the housing are coupled to each other by a
welding or caulking process.

29. The method according to claim 26, wherein the guide portion is formed through a deep drawing process.

INTERNATIONAL SEARCH REPORT

International application No.
PCT/KR2004/003225

A. CLASSIFICATION OF SUBJECT MATTER**IPC7 H02K 37/04**

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: H20K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Korean Patents and application for inventions since 1975

Korean Utility Modles and application for Utility for Utility Models since 1975

Japanese Utility modles and application for Utility for Utility models since 1975

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 6157103 A (MITSUBISHI DENKI) 5 DEC. 2000 Figs. 1, 9, 10, Claims 1-4	1, 5, 6, 8, 18, 22
A	US 5845390 A (CHÜN-YING CHENG) 8 DEC. 1998 Abstract, Claim 1	24
A	JP 62-285657 A (TOKYO SOKUHAN) 11 DEC. 1987 Figs 1, 5, 7, Claims 1-3	1, 5, 6, 8
A	JP 07-308051 A (SONY CO., LTD.) 21 NOV. 1995 Abstract, Claims 1-6	24
A	JP 11-308845 A (TAMAGAWA SEIKI CO., LTD.) 5 NOV. 1999 See the whole document	1
A	US 4528473 A (SHINANO KENSHI) 9 JUL. 1985 See the whole document	1

☐ Further documents are listed in the continuation of Box C.☐ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

23 MARCH 2005 (23.03.2005)

Date of mailing of the international search report

24 MARCH 2005 (24.03.2005)

Name and mailing address of the ISA/KR



Korean Intellectual Property Office
920 Dunsan-dong, Seo-gu, Daejeon 302-701,
Republic of Korea

Facsimile No. 82-42-472-7140

Authorized officer

JEON, Yong Hai

Telephone No. 82-42-481-5657

